

# **VERSA-LINE PLATFORM**





Fuel fill is recessed in rub rail

## **PLATFORM FEATURES**

- Constructed of an all steel underframe
- Stake pockets on 24" centers
- Tapered corners
- Weather-resistant, plug-in wiring harness
- Rubber mounted lights to FMVSS specifications



### **STAKE BODY FEATURES**

- 30" to 40" stake sides
- Stake pockets will accept 2" x 4" lumber
- Slats are made of ribbed steel for strength and durability (Optional wood slats are available.)
- Swing gate & hold down latch are standard
- Latch assembly secures corners and sides for less noise & more cargo protection

Rubber mounted lights to FMVSS specifications

### **PLATFORM & STAKE BODY FEATURES**

- Floors feature CCA treated water repellent 2" tongue and groove floor boards (Optional smooth or treadplate steel is available.)
- 5" x 10 gauge steel side & end rails
- 3" structural channel crossmembers on 12" centers
- Structural channel longsills (6" to 8") are gussetted to every crossmember for strength
- Front & rear crossmember give added floor strength
- Body is hoist compatible
- Standard sizes available from 7' x 78" to 24' x 96" (Others upon request.)





## **VERSA-LINE PLATFORM BODY OPTIONS**

Versa-Line Stake Rack Specifications			
INTERIOR LENGTH	6" less than platform length		
INTERIOR WIDTH	96″ O.D. x 90″ I.D.		
SLATS	6" x 16" gauge roll-formed steel or 1" x 6" pine		
STAKES	14 gauge roll-formed with liners		
FRONT	12 gauge bulkhead with window (standard); stake front optional		
REARS	Hinged, swing out		
HARDWARE	Spring-loaded, western-style gate locks on swing gate and rears		
HOLD DOWN LATCH	Spring-loaded in stake, 1 per section		
STANDARD HEIGHTS	40" (GM 3500 and Ford Super Duty); 42" (GM 4500/5500)		
SIDE SECTIONS	7'-10' 2-piece sides 12'-20' 3-piece sides/1 swing gate per side 22'-24' 4-piece sides/1 swing gate per side		

Versa-Line Contractor Rack Specifications					
	FOLD DOWN STYLE	LIFTOUT STYLE			
INTERIOR LENGTH	6" less than platform length	6" less than platform length			
INTERIOR WIDTH	96″ O.D. x 90″ I.D.	87¼″ O.D. x 81¼″ I.D. or 96″ O.D. x 90″ I.D.			
SIDES	16" high x 12 gauge formed steel with 14 gauge stakes	14" high x 12 gauge formed steel with 14 gauge stakes			
TAILGATE	16" high x 12 gauge formed steel, double-acting	14" high x 12 gauge formed steel, double-acting			
FRONT	12 gauge roll-formed bulkhead with window	12 gauge roll-formed bulkhead with window			

Versa-Line Grain Rack Specifications				
	<u>42" HIGH</u>	<u>52" HIGH</u>	<u>10" TIP TOP</u>	
INTERIOR LENGTH	6" less than platform length	6" less than platform length	6" less than platform length	
INTERIOR WIDTH	87¼″ O.D. x 81¼″ I.D. or 96″ O.D. x 90″ I.D.	90″	90″	
PANEL SKINS	16 gauge roll-formed	14 gauge roll-formed	16 gauge roll-formed	
STAKES	14 gauge with liners	14 gauge with liners	14 gauge	
REAR	2 wings, 39 <sup>5</sup> /8" x 32" high grain gate 10" filler panel, bull bar	2 wings, 39 <sup>5</sup> /s" x 32" high grain gate 20" filler panel, bull bar	1 piece, full-width	

Kneebraced Bulkhead Specifications				
	STANDARD DUTY	HEAVY DUTY		
HEIGHT	32″, 42″ or 52″	42", 52" or 62"		
WIDTH	72", 78", 87¼" or 96"	87¼″ or 96″		
PANEL SKINS	12 gauge formed steel	<sup>3</sup> / <sub>16</sub> " formed steel		
STAKES	14 gauge roll-formed steel with liners	14 gauge roll-formed steel with liners		
WINDOW	Full width covered with expanded metal	Full width covered with expanded metal		

#### FOR MORE INFORMATION, CONTACT YOUR NEAREST MTE LOCATION:

MONROE 1051 W. 7Tth Street Monroe, WI 53566 PH: 800-978-8785 MARSHFIELD 1601 E. 29th Street Marshfield, WI 5444 PH: 800-882-1900

**DEPERE** 1151 W. Main Av 9 DePere, WI 54 PH: 877-814-7

**JOLIET** 812 Draper Avenu Joliet, IL 60432 PH: 800-892-705 FLINT 2400 Reo Drive Flint, MI 48507 PH: 877-233-2030 LOUISVILLE 12001 Westport Louisville, KY 402 PH: 800-978-87 LITCHFIELD - TOWMASTER

61381 US Hwy Litchfield, MN 55 PH: 888-878-8

#### KERNERSVILLE - SOUTHERN COACH

960 Old Winston Road Kernersville, NC 27284 PH: 336-996-6807